

Town of Berlin

Stormwater Infrastructure Mapping Project

April 2013



***VTDEC – CLEAN WATER INITIATIVE PROGRAM,
WATERSHED MANAGEMENT DIVISION***

<https://dec.vermont.gov/water-investment/cwi/solutions/developed-lands/idde>

Jim Pease, Jim.Pease@vermont.gov
David Ainley, David.Ainley@vermont.gov

Overview

This stormwater infrastructure mapping project was completed for the municipality by the Agency of Natural Resources Ecosystems Restoration program to supplement the existing drainage data collected by the town and with the intention of providing a tool for planning, maintenance, and inspection of the stormwater infrastructure.

The GIS maps and geodatabase are meant to provide an overall picture and understanding of the connectivity or connectedness of the storm system on both public and private properties in order to raise the awareness of the need for regular maintenance. The generation and transport of nonpoint source pollution increases with increasing connectivity of a drainage system. Having an understanding of the connectedness of the system is also a valuable tool for hazardous material spill planning and prevention. Knowledge of the extent of the system is also essential for the detection and elimination of illicit discharges. Outfall locations and system connectedness data are used as a base for locating illicit or illegal discharges of non-stormwater to the municipal storm system and tracing them up to the source. Knowledge of which areas of the sewer service area have combined stormwater and sewer systems can better assist the municipality in planning and implementing combined sewer separation projects. Knowledge of the layout and extent of the stormwater system can inform options for cleaning up existing polluted stormwater discharges. This project provides information and guidance for potential retrofit treatment locations and opportunities. Knowledge of where storm drains are located can also assist municipalities and residents with emergency preparedness for large rainfall events (i.e. Tropical Storm or Hurricanes) or spring snowmelt runoff events. By keeping storm drains clean, clear and open a good deal of localized flooding could be prevented. Finally, by providing a more thorough understanding of the system it is the hope that this project could be the basis for a local stormwater ordinance or be used to help enhance an existing stormwater management program.

Project Summary

The principal goal of this project was to develop up to date municipal drainage maps. These drainage maps were created showing the paths that stormwater runoff travels from where it falls on impervious surfaces such as parking lots, roads, and rooftops, to the outfall points in various receiving waters. These maps show the stormwater infrastructure including features like pipes, manholes, catchbasins, and swales within a municipality. Data sources included data collected from field work, a mapping grade Trimble GPS unit, available state permit plans, record drawings, town plans, WWMD plans, existing GIS data from contractors, and the input and guidance of knowledgeable members from the municipalities.

A second goal of this project was to establish potential locations for Best Management Practice (BMP) stormwater retrofit sites. These are sites where stormwater treatment structures could be added and where they would be most cost effective and efficient for sediment and phosphorus or nitrogen removal. In order to develop a retrofit site list, drainage area subwatersheds were delineated around the drainage networks. Determining how the stormwater infrastructure was connected was necessary in determining the subwatershed drainage areas within the town.

Delineating the drainage areas was done using the stormwater infrastructure maps, along with satellite imagery, a Digital Elevation Model (DEM), and USGS topographic maps. These data sources were used to approximate where the land area within each municipality was draining to; as well as where the high points were that divided the sub-drainage areas. The

completed maps show the drainage coverage for essentially the entire municipality, but with a focus on areas with greater concentrations of impervious cover.

Impervious cover layers were created by either hand digitization or by using a method of raster pixel calculation (with ArcGIS spatial analyst extension) to create a vegetation index from the National Agricultural Imagery Program (NAIP) 08 orthophotos. The area which contrasted with the vegetation represents impervious surfaces and was then modified with buffered water and roads layers to make it more accurate. A more detailed explanation of this process is available in a separate document. The impervious layer was used to calculate the percent of each delineated drainage area that would generate stormwater runoff. The percentage of impervious surface number for each subwatershed was then adjusted with a connectivity rating. A rating was assigned to each drainage area polygon describing how directly connected the impervious surfaces within that subwatershed are to the receiving water. By adjusting the percent impervious area numbers with this connectivity rating the effective impervious area (EIA) was established for each subwatershed (Sutherland, 1995). This effective impervious number is a more accurate description of the amount of runoff produced by each of the subwatersheds because it helps to take factors such as infiltration into account.

After the effective impervious numbers were calculated for the subwatersheds the Simple Method was used to estimate the annual sediment (TSS) and phosphorus (TP) or Nitrogen (TN) loads generated by each subwatershed. The Simple method uses information which includes the adjusted impervious value, average annual rainfall for the location, total subwatershed area, and a given pollutant concentration value to calculate an annual load for various pollutants (Schueler, 1987). Pollutant loads estimated by the Simple Method in this project are planning level estimates and are meant to give a general idea of the amounts of sediment or nutrient wash-off produced by each subwatershed for prioritization purposes. Subwatersheds were then prioritized, using the loading calculations as well as other criteria, and given Action List numbers ranging from 1 to 3 (one being the highest priority). The Action List number depends both upon loading values and feasibility of potential retrofit treatment options. Potential retrofit options listed in the TARGET maps are based on field observations and not on actual availability of land or willingness of landowner.

Water Quality Volume (WQv – the amount of storage needed to treat stormwater from a 0.9 inch storm) and Channel Protection Volume (CPv – the volume of storage that is needed to hold and slowly release stormwater for a 2.1 inch rain event) were also calculated for delineated subwatershed areas. CPv calculations are only applicable if the receiving water is not a large body of water and is therefore susceptible to channel erosion. These numbers were used in the retrofit recommendation process because the volume of water to be treated was a key factor in determining the type of retrofit.

Project References

Schueler, T. 1987. Technical Documentation of a Simple Method for Estimating Urban Storm Pollutant Export. Controlling Urban Runoff: A Practical Manual for Planning and Designing Urban BMPs. Appendix A.

Schueler, T. et al., 2007. Urban Stormwater Retrofit Practices, Version 1.0. Manual 3, Center for Watershed Protection, August 2007.

Sutherland, R. 1995. Methodology for Estimating the Effective Impervious Area of Urban Watersheds. Technical Note 58 – Pervious Area Management. Watershed Protection Techniques. Vol. 2, No. 1

***All data was created in an ArcGIS 10 Geodatabase format and is available from VTDEC.**

Main Lake and Winooski River Nonpoint Phosphorus Overview

LAND USE TYPES

| | | | | | |
|--|--|--|--|--|--|
| DEVELOPED All roads, cities, suburbs, lawns and large-lot buildings. | | AGRICULTURE Crop and livestock production. | | FORESTED Areas covered primarily with trees. | |
|--|--|--|--|--|--|




Figure shows the breakdown of contributions from developed, agricultural and forested land sources in the Main Lake-Winooski River Watershed to Total Phosphorus loading of the Main Lake, VT side.

MAIN LAKE

| STATUS | TREND |
|--------|-------|
| | |
| | |
| | |

*The LaPlatte R. has improved, but no other rivers show a trend

| | |
|--|--|
| | |
| | |
| | |

INDICATORS by LAKE SEGMENT

| | |
|---|-------------------|
| Phosphorus in Lake (p. 5) | PHOSPHORUS |
| Nonpoint source loading to Lake (p. 7-8) | |
| Wastewater facility loading to Lake (p. 10) | |

| | |
|--|----------------------------------|
| Beach closures from bacteria [^] (p. 12-13) | HUMAN HEALTH & TOXINS |
| Cyanobacteria blooms [^] (p. 14) | |
| Fish advisories for toxins [^] (p. 14) | |

* Figures taken from Lake Champlain Basin Program – State of the Lake and Ecosystem Indicators Report (2012).
<http://sol.lcbp.org/>

| STATUS | TREND |
|-----------------------------|--|
| GOOD | IMPROVING |
| FAIR | NO TREND (neither improving nor deteriorating) |
| POOR | DETERIORATING |
| NO STATUS DATA IS AVAILABLE | NO TREND DATA IS AVAILABLE |

Subwatershed Data

*Tables showing calculations and
Priority drainage area retrofit possibilities*

This is a key showing the abbreviations of the different stormwater treatment structures or practices listed in the calculation sheets.

| Abbreviation Key | |
|-------------------------|---|
| Code | Structure Type |
| BB | Baffle Box |
| BFCB | Baffled Catchbasin |
| BR | Bioretention Area (aka Bioretention Filter) |
| BS | Buffer Strip (25' Min.) |
| CB | Catch Basin |
| CBI | Catch Basin Insert |
| CD | Check Dam |
| DG | Detention Gallery |
| DI | Drop Inlet |
| DP | Dry Pond |
| DS | Dry Swale |
| DW | Drywell |
| EDPMP | Extended Detention Pond with Micropool (aka Micropool Extended Detention Basin) |
| GS | Grass Swale (aka Open Channel) |
| IB | Infiltration Basin |
| IG | Infiltration Gallery |
| IP | Infiltration Pipe |
| OF | Overland Flow |
| OGF | Organic Filter |
| POP | Pocket Pond |
| PP | Perforated Pipe |
| RDD | Roof Drain Disconnect |
| RR | Rock Riprap |
| RS | Riprap Swale |
| SB | Sediment Basin |
| SF | Sand Filter (aka Surface Sand Filter) |
| SS-SF | Swirl Separator – Sand Filter |
| ST | Septic Tank |
| SWPPP | Stormwater Pollution Prevention Plan |
| TT | Treatment Tank |
| WL | Wetland (Constructed) |
| WP | Wet Pond (Retention) |
| WS | Wet Swale |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | | | | | | | | |
|--|---------------|---|--|-------------------------------|------------------------|--------------------------------------|---|--|---|--|----------------------------------|--------------------------------|
| Watershed Number | Action List # | Proposed Action | Proposed or Existing Stormwater Treatment Practice | Permit Number | Watershed Area (Acres) | Percent Mapped Impervious Area (MIA) | Sediment Load with Current Reductions (lbs) | Sediment Load with Priority Action (lbs) | Phosphorus Load with Current Reductions (lbs) | Phosphorus Load with Priority Action (lbs) | Water Quality Volume (Acre-Feet) | Channel Protection (Acre-Feet) |
| 2 Berlin | | | WP/RS/SB/SWPP P | 4365-9003/4365-9010 | 8.1 | 63 | 4,970 | 4,970 | 13.8 | 13.8 | 0.28 | 0.56 |
| 3 Berlin | | | WP/IG/UD/SWPPP | 4582-9003/4582-9015/4582-9010 | 66.7 | 23 | 4,329 | 4,329 | 14.4 | 14.4 | 0.49 | 1.69 |
| 4 Berlin | | | WP/IG/UD/SWPPP | 4582-9003/4582-9015/4582-9010 | 49.6 | 38 | 6,005 | 6,005 | 20.0 | 20.0 | 0.68 | 2.09 |
| 5 Berlin | | | UD/SWPPP | 4582-9003/4582-9015/4582-9010 | 4.9 | 1 | 329 | 329 | 0.9 | 0.9 | 0.02 | 0.01 |
| 6 Berlin | | | OF | | 268.6 | 5 | 21,387 | 21,387 | 59.4 | 59.4 | 1.21 | 1.48 |
| 7 Berlin | | | CB/GS | | 15.6 | 37 | 5,183 | 5,183 | 14.4 | 14.4 | 0.29 | 0.63 |
| 8 Berlin | | | GS | | 4.3 | 20 | 759 | 759 | 2.1 | 2.1 | 0.04 | 0.10 |
| 9 Berlin | | | GS/CB/EDP | 3002-9010 | 2.9 | 65 | 1,669 | 1,669 | 4.6 | 4.6 | 0.09 | 0.21 |
| 10 Berlin | | | GS/CB/EDP | 3002-9010 | 6.4 | 69 | 4,041 | 4,041 | 11.2 | 11.2 | 0.23 | 0.48 |
| 11 Berlin | | | GS/WP/CB | 5176-9015 | 8.5 | 49 | 600 | 600 | 5.0 | 5.0 | 0.17 | 0.46 |
| 12 Berlin | | | OF | | 3.7 | 44 | 1,529 | 1,529 | 4.2 | 4.2 | 0.09 | 0.18 |
| 13 Berlin | 2 | Modify outlet of EDP, Combine with 21,153 | EDPMP/CB/GS | 3243-9010 | 18.4 | 19 | 2,021 | 1,010 | 5.6 | 3.9 | 0.11 | 0.39 |
| 14 Berlin | | | GS/CB | | 2.3 | 73 | 1,898 | 1,898 | 5.3 | 5.3 | 0.11 | 0.19 |
| 15 Berlin | | | OF | | 0.2 | 80 | 212 | 212 | 0.6 | 0.6 | 0.01 | 0.02 |
| 16 Berlin | | | GS/EDP | | 0.5 | 73 | 333 | 333 | 0.9 | 0.9 | 0.02 | 0.04 |
| 17 Berlin | | | OF | | 3.7 | 37 | 1,275 | 1,275 | 3.5 | 3.5 | 0.07 | 0.15 |
| 18 Berlin | | | CB | | 1.0 | 85 | 1,036 | 1,036 | 2.9 | 2.9 | 0.06 | 0.09 |
| 19 Berlin | | | CB | | 0.6 | 88 | 631 | 631 | 1.8 | 1.8 | 0.04 | 0.06 |
| 20 Berlin | 2 | Bioretention in median of Route 62 | EDPMP/GS/CB | | 5.5 | 41 | 2,626 | 1,313 | 7 | 5.1 | 0.15 | 0.25 |
| 21 Berlin | 2 | Combine with 13,153 | EDPMP/CB/GS | | 2.1 | 52 | 823 | 412 | 1.4 | 1.0 | 0.05 | 0.12 |
| 22 Berlin | | | WL/GS/CB | 3799-9010 | 26.3 | 32 | 979 | 979 | 13.6 | 13.6 | 0.28 | 0.92 |
| 23 Berlin | | | GS | | 5.6 | 24 | 1,144 | 1,144 | 3.2 | 3.2 | 0.06 | 0.15 |
| 26 Berlin | | | OF | | 74.6 | 2 | 5,133 | 5,133 | 14.3 | 14.3 | 0.29 | 0.14 |
| 27 Berlin | | | CB/OF | 6689-9015 | 0.6 | 101 | 142 | 142 | 1.2 | 1.2 | 0.04 | FALSE |
| 28 Berlin | | | GS/EDP | 6689-9015 | 1.1 | 78 | 180 | 180 | 1.5 | 1.5 | 0.05 | 0.10 |
| 29 Berlin | | | GS/EDP | 4244-9015 | 0.5 | 16 | 9 | 9 | 0.1 | 0.1 | 0.00 | 0.01 |
| 30 Berlin | | | GS/EDP | 4244-9015 | 0.9 | 71 | 118 | 118 | 1.0 | 1.0 | 0.03 | 0.07 |
| 31 Berlin | | | GS | | 1.2 | 65 | 861 | 861 | 2.4 | 2.4 | 0.05 | 0.09 |
| 32 Berlin | | | GS | | 2.2 | 59 | 1,317 | 1,317 | 3.7 | 3.7 | 0.07 | 0.14 |
| 33 Berlin | | | GS/WP/CB | 3933-9015 | 5.1 | 56 | 444 | 444 | 3.7 | 3.7 | 0.13 | 0.31 |
| 34 Berlin | | | OF/GS | 6689-9015 | 8.8 | 37 | 2,932 | 2,932 | 8.1 | 8.1 | 0.17 | 0.36 |
| 35 Berlin | | | GS | | 2.6 | 38 | 882 | 882 | 2.4 | 2.4 | 0.05 | 0.11 |
| 36 Berlin | | | CB/GS/WP/SWPP P | 3909-9015/5409-9003 | 5.8 | 83 | 1,042 | 1,042 | 8.7 | 8.7 | 0.29 | 0.53 |
| 37 Berlin | | | OF | | 2.8 | 63 | 1,888 | 1,888 | 5.2 | 5.2 | 0.11 | 0.20 |
| 38 Berlin | | | GS/CB/OF | | 24.3 | 50 | 11,923 | 11,923 | 33.1 | 33.1 | 0.67 | 1.34 |
| 39 Berlin | | | GS/WP/CB | 4104-9015 | 13.5 | 25 | 1,346 | 1,346 | 4.5 | 4.5 | 0.11 | 0.38 |
| 40 Berlin | | | OF | | 4.8 | 59 | 2,927 | 2,927 | 8.1 | 8.1 | 0.17 | 0.31 |
| 41 Berlin | | | GS/WP | 5471-9010 | 5.7 | 14 | 523 | 523 | 1.5 | 1.5 | 0.03 | 0.09 |
| 42 Berlin | | | SB/CB/GS/SWPPP | 4997-9003 | 10.4 | 50 | 4,567 | 4,567 | 12.7 | 12.7 | 0.26 | 0.58 |
| 45 Berlin | | | GS | | 0.5 | 39 | 185 | 185 | 0.5 | 0.5 | 0.01 | 0.02 |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | | | | | |
|--|---------------|--|-----------------------------------|---------------------------------------|--|--|------------------------|---|-----------------|
| Watershed Number | Action List # | Proposed or Existing Stormwater Treatment Practice | Estimated Basin Construction Cost | Estimated Other BMP Construction Cost | Cost of Sediment Removal Per Pound (based on annual sediment load) | Cost of Phosphorus Removal Per Pound (based on annual phosphorus load) | Assistance Program | Number of LID - Roof Raingardens to treat CPv (Residential) | Raingarden Cost |
| 2 Berlin | 0 | WP/RS/SB/SWPPP | | | | | | 281 | \$129,185 |
| 3 Berlin | 0 | WP/IG/UD/SWPPP | | | | | | 846 | \$389,355 |
| 4 Berlin | 0 | WP/IG/UD/SWPPP | | | | | | 1,047 | \$481,742 |
| 5 Berlin | 0 | UD/SWPPP | | | | | | 3 | \$1,235 |
| 6 Berlin | 0 | OF | | | | | | 739 | \$339,796 |
| 7 Berlin | 0 | CB/GS | | | | | | 316 | \$145,164 |
| 8 Berlin | 0 | GS | | | | | | 48 | \$22,225 |
| 9 Berlin | 0 | GS/CB/EDP | | | | | | 105 | \$48,219 |
| 10 Berlin | 0 | GS/CB/EDP | | | | | | 241 | \$111,067 |
| 11 Berlin | 0 | GS/WP/CB | | | | | | 229 | \$105,553 |
| 12 Berlin | 0 | OF | | | | | | 89 | \$41,130 |
| 13 Berlin | 2 | EDPMP/CB/GS | 96,333.53 | | \$40 | \$23,867 | ERP, Section 319, LCBP | 193 | \$88,955 |
| 14 Berlin | 0 | GS/CB | | | | | | 94 | \$43,212 |
| 15 Berlin | 0 | OF | | | | | | 10 | \$4,670 |
| 16 Berlin | 0 | GS/EDP | | | | | | 19 | \$8,777 |
| 17 Berlin | 0 | OF | | | | | | 77 | \$35,560 |
| 18 Berlin | 0 | CB | | | | | | 46 | \$21,156 |
| 19 Berlin | 0 | CB | | | | | | 28 | \$12,828 |
| 20 Berlin | 2 | EDPMP/GS/CB | 57,050.71 | | \$43 | \$26,069 | ERP, Section 319, LCBP | 124 | \$57,051 |
| 21 Berlin | 2 | EDPMP/CB/GS | Combine with 13,153 | | | | | 61 | \$27,851 |
| 22 Berlin | 0 | WL/GS/CB | | | | | | 459 | \$210,926 |
| 23 Berlin | 0 | GS | | | | | | 73 | \$33,647 |
| 26 Berlin | 0 | OF | | | | | | 68 | \$31,115 |
| 27 Berlin | 0 | | | | | | | 0 | \$0 |
| 28 Berlin | 0 | GS/EDP | | | | | | 49 | \$22,394 |
| 29 Berlin | 0 | GS/EDP | | | | | | 4 | \$1,913 |
| 30 Berlin | 0 | GS/EDP | | | | | | 34 | \$15,867 |
| 31 Berlin | 0 | GS | | | | | | 44 | \$20,424 |
| 32 Berlin | 0 | GS | | | | | | 71 | \$32,465 |
| 33 Berlin | 0 | GS/WP/CB | | | | | | 156 | \$71,682 |
| 34 Berlin | 0 | OF/GS | | | | | | 178 | \$82,035 |
| 35 Berlin | 0 | GS | | | | | | 53 | \$24,588 |
| 36 Berlin | 0 | CB/GS/WP/SWPPP | | | | | | 267 | \$122,827 |
| 37 Berlin | 0 | OF | | | | | | 99 | \$45,350 |
| 38 Berlin | 0 | GS/CB/OF | | | | | | 671 | \$308,670 |
| 39 Berlin | 0 | GS/WP/CB | | | | | | 188 | \$86,311 |
| 40 Berlin | 0 | OF | | | | | | 156 | \$71,851 |
| 41 Berlin | 0 | GS/WP | | | | | | 46 | \$20,987 |
| 42 Berlin | 0 | SB/CB/GS/SWPPP | | | | | | 288 | \$132,392 |
| 45 Berlin | 0 | GS | | | | | | 11 | \$5,120 |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | | | (pg2) | | | | | |
|--|---------------|---|--|---------------|------------------------|--------------------------------------|---|--|---|--|----------------------------------|--------------------------------|
| Watershed Number | Action List # | Proposed Action | Proposed or Existing Stormwater Treatment Practice | Permit Number | Watershed Area (Acres) | Percent Mapped Impervious Area (MIA) | Sediment Load with Current Reductions (lbs) | Sediment Load with Priority Action (lbs) | Phosphorus Load with Current Reductions (lbs) | Phosphorus Load with Priority Action (lbs) | Water Quality Volume (Acre-Feet) | Channel Protection (Acre-Feet) |
| 46 Berlin | | | CB | | 1.9 | 37 | 632 | 632 | 1.8 | 1.8 | 0.04 | 0.08 |
| 47 Berlin | | | CB/OF | | 3.5 | 38 | 1,227 | 1,227 | 3.4 | 3.4 | 0.07 | 0.15 |
| 48 Berlin | | | CB/GS/OF | | 8.1 | 32 | 2,237 | 2,237 | 6.2 | 6.2 | 0.13 | 0.28 |
| 49 Berlin | | | GS | | 2.6 | 26 | 600 | 600 | 1.7 | 1.7 | 0.03 | 0.08 |
| 50 Berlin | | | GS | | 9.3 | 18 | 1,493 | 1,493 | 4.1 | 4.1 | 0.08 | 0.19 |
| 51 Berlin | | | OF/WP | | 53.9 | 10 | 4,221 | 4,221 | 11.7 | 11.7 | 0.24 | 0.60 |
| 52 Berlin | | | OF | | 36.3 | 7 | 3,285 | 3,285 | 9.1 | 9.1 | 0.19 | 0.30 |
| 53 Berlin | | | WP/CB/GS | 3761-9010 | 27.2 | 62 | 2,880 | 2,880 | 24.0 | 24.0 | 0.81 | 1.86 |
| 55 Berlin | | | GS | | 8.1 | 49 | 3,841 | 3,841 | 10.7 | 10.7 | 0.22 | 0.44 |
| 56 Berlin | | | BRA/GS/CB | 3825-9015 | 3.4 | 96 | 795 | 795 | 6.6 | 6.6 | 0.22 | 0.36 |
| 57 Berlin | | | CB | | 0.2 | 76 | 219 | 219 | 0.6 | 0.6 | 0.01 | 0.02 |
| 58 Berlin | | | CB | | 1.3 | 66 | 1,014 | 1,014 | 2.8 | 2.8 | 0.06 | 0.09 |
| 59 Berlin | | | GS | 6720-9015 | 2.0 | 86 | 944 | 944 | 3.9 | 3.9 | 0.11 | 0.19 |
| 60 Berlin | 2 | Bioretention at front of dealership | BRA/GS | 6720-9015 | 2.0 | 83 | 893 | 179 | 3.7 | 2.6 | 0.10 | 0.18 |
| 61 Berlin | | | OF/GS | | 2.4 | 66 | 1,678 | 1,678 | 4.7 | 4.7 | 0.09 | 0.17 |
| 62 Berlin | 2 | Bioretention below rear parking lot | BRA/GS/IB/CB | 3064-9015 | 3.0 | 57 | 274 | 55 | 2.3 | 1.6 | 0.08 | 0.19 |
| 63 Berlin | | | CB | 3064-9010 | 3.6 | 89 | 4,009 | 4,009 | 11.1 | 11.1 | 0.23 | 0.35 |
| 64 Berlin | | | CB | | 1.0 | 91 | 1,106 | 1,106 | 3.1 | 3.1 | 0.06 | 0.10 |
| 65 Berlin | | | CB | | 9.6 | 41 | 4,603 | 4,603 | 12.8 | 12.8 | 0.26 | 0.43 |
| 66 Berlin | 1 | Bioretention at 765 Granger Rd | BRA/CB/GS | | 7.2 | 51 | 4,288 | 858 | 11.9 | 9.5 | 0.24 | 0.40 |
| 67 Berlin | | | CB | 3064-9010 | 2.8 | 83 | 2,839 | 2,839 | 7.9 | 7.9 | 0.16 | 0.25 |
| 68 Berlin | | | URB/CB/GS | 3064-9010 | 3.9 | 84 | 3,734 | 3,734 | 10.4 | 10.4 | 0.21 | 0.36 |
| 69 Berlin | | | CB | | 6.4 | 20 | 1,114 | 1,114 | 3.1 | 3.1 | 0.06 | 0.14 |
| 70 Berlin | | | CB | | 0.2 | 82 | 252 | 252 | 0.7 | 0.7 | 0.01 | 0.02 |
| 71 Berlin | | | OF/GS | | 48.6 | 10 | 5,168 | 5,168 | 14.4 | 14.4 | 0.29 | 0.56 |
| 72 Berlin | | | GS | | 2.9 | 35 | 929 | 929 | 2.6 | 2.6 | 0.05 | 0.11 |
| 73 Berlin | 1 | Extended Detention Pond in median of Rte 62 | EDPMP/CB/GS | | 9.1 | 32 | 2,600 | 520 | 7.2 | 4.3 | 0.15 | 0.32 |
| 74 Berlin | | | CB/GS | | 1.7 | 51 | 870 | 870 | 2.4 | 2.4 | 0.05 | 0.10 |
| 75 Berlin | | | OF | | 11.2 | 10 | 1,185 | 1,185 | 3.3 | 3.3 | 0.07 | 0.13 |
| 76 Berlin | | | CB/GS | | 0.8 | 14 | 97 | 97 | 0.3 | 0.3 | 0.01 | 0.01 |
| 77 Berlin | | | CB/GS | | 0.8 | 36 | 258 | 258 | 0.7 | 0.7 | 0.01 | 0.03 |
| 78 Berlin | | | CB/GS | | 4.5 | 16 | 630 | 630 | 1.7 | 1.7 | 0.04 | 0.08 |
| 79 Berlin | | | GS | | 8.3 | 3 | 606 | 606 | 1.7 | 1.7 | 0.03 | 0.03 |
| 80 Berlin | | | GS | | 7.4 | 7 | 644 | 644 | 1.8 | 1.8 | 0.04 | 0.05 |
| 81 Berlin | | | OF/GS | | 16.0 | 16 | 2,302 | 2,302 | 6.4 | 6.4 | 0.13 | 0.28 |
| 82 Berlin | | | GS | 5160-9010 | 5.4 | 14 | 708 | 708 | 2.0 | 2.0 | 0.04 | 0.09 |
| 83 Berlin | | | OF | | 50.5 | 6 | 4,230 | 4,230 | 11.7 | 11.7 | 0.24 | 0.33 |
| 84 Berlin | | | GS/OF | | 25.4 | 5 | 2,032 | 2,032 | 5.6 | 5.6 | 0.11 | 0.14 |
| 85 Berlin | | | OF/CB | | 70.6 | 16 | 10,121 | 10,121 | 28.1 | 28.1 | 0.57 | 1.25 |
| 86 Berlin | | | OF | | 20.2 | 10 | 2,085 | 2,085 | 5.8 | 5.8 | 0.12 | 0.22 |
| 87 Berlin | | | OF | | 14.0 | 11 | 1,551 | 1,551 | 4.3 | 4.3 | 0.09 | 0.17 |
| 88 Berlin | | | GS/WP | 6929-9015 | 46.7 | 12 | 791 | 791 | 6.6 | 6.6 | 0.22 | 0.64 |
| 89 Berlin | | | GS/CB | | 5.4 | 22 | 1,030 | 1,030 | 2.9 | 2.9 | 0.06 | 0.13 |
| 90 Berlin | | | CB/GS/OF | | 39.9 | 6 | 3,360 | 3,360 | 9.3 | 9.3 | 0.19 | 0.27 |
| 91 Berlin | | | GS | | 1.9 | 25 | 404 | 404 | 1.1 | 1.1 | 0.02 | 0.05 |
| 92 Berlin | | | GS | | 0.7 | 30 | 197 | 197 | 0.5 | 0.5 | 0.01 | 0.02 |
| 93 Berlin | | | GS/CB | | 4.5 | 27 | 1,045 | 1,045 | 2.9 | 2.9 | 0.06 | 0.13 |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | (pg2) | | | | |
|--|---------------|--|-----------------------------------|---------------------------------------|--|--|------------------------|---|-----------------|
| Watershed Number | Action List # | Proposed or Existing Stormwater Treatment Practice | Estimated Basin Construction Cost | Estimated Other BMP Construction Cost | Cost of Sediment Removal Per Pound (based on annual sediment load) | Cost of Phosphorus Removal Per Pound (based on annual phosphorus load) | Assistance Program | Number of LID - Roof Raingardens to treat CPv (Residential) | Raingarden Cost |
| 46 Berlin | 0 | CB | | | | | | 38 | \$17,667 |
| 47 Berlin | 0 | CB/OF | | | | | | 74 | \$34,097 |
| 48 Berlin | 0 | CB/GS/OF | | | | | | 140 | \$64,311 |
| 49 Berlin | 0 | GS | | | | | | 38 | \$17,555 |
| 50 Berlin | 0 | GS | | | | | | 94 | \$43,324 |
| 51 Berlin | 0 | OF/WP | | | | | | 298 | \$137,006 |
| 52 Berlin | 0 | OF | | | | | | 149 | \$68,362 |
| 53 Berlin | 0 | WP/CB/GS | | | | | | 932 | \$428,718 |
| 55 Berlin | 0 | GS | | | | | | 218 | \$100,209 |
| 56 Berlin | 0 | BRA/GS/CB | | | | | | 180 | \$82,879 |
| 57 Berlin | 0 | CB | | | | | | 9 | \$4,332 |
| 58 Berlin | 0 | CB | | | | | | 46 | \$21,324 |
| 59 Berlin | 0 | GS | | | | | | 94 | \$43,099 |
| 60 Berlin | 2 | BRA/GS | 23,248.55 | | \$33 | \$20,821 | ERP, Section 319, LCBP | 92 | \$42,368 |
| 61 Berlin | 0 | OF/GS | | | | | | 86 | \$39,611 |
| 62 Berlin | 2 | BRA/GS/IB/CB | 17,843.91 | | \$81 | \$26,026 | ERP, Section 319, LCBP | 95 | \$43,662 |
| 63 Berlin | 0 | CB | | | | | | 177 | \$81,472 |
| 64 Berlin | 0 | CB | | | | | | 49 | \$22,394 |
| 65 Berlin | 0 | CB | | | | | | 217 | \$99,983 |
| 66 Berlin | 1 | BRA/CB/GS | 55,799.49 | | \$16 | \$23,423 | ERP, Section 319, LCBP | 200 | \$92,162 |
| 67 Berlin | 0 | CB | | | | | | 126 | \$58,178 |
| 68 Berlin | 0 | URB/CB/GS | | | | | | 180 | \$82,822 |
| 69 Berlin | 0 | CB | | | | | | 71 | \$32,578 |
| 70 Berlin | 0 | CB | | | | | | 11 | \$5,176 |
| 71 Berlin | 0 | OF/GS | | | | | | 278 | \$127,891 |
| 72 Berlin | 0 | GS | | | | | | 57 | \$26,220 |
| 73 Berlin | 1 | EDPMP/CB/GS | 44,860.73 | | \$22 | \$15,527 | ERP, Section 319, LCBP | 162 | \$74,495 |
| 74 Berlin | 0 | CB/GS | | | | | | 49 | \$22,394 |
| 75 Berlin | 0 | OF | | | | | | 64 | \$29,314 |
| 76 Berlin | 0 | CB/GS | | | | | | 6 | \$2,644 |
| 77 Berlin | 0 | CB/GS | | | | | | 16 | \$7,258 |
| 78 Berlin | 0 | CB/GS | | | | | | 39 | \$17,836 |
| 79 Berlin | 0 | GS | | | | | | 15 | \$6,752 |
| 80 Berlin | 0 | GS | | | | | | 27 | \$12,435 |
| 81 Berlin | 0 | OF/GS | | | | | | 142 | \$65,436 |
| 82 Berlin | 0 | GS | | | | | | 43 | \$19,637 |
| 83 Berlin | 0 | OF | | | | | | 166 | \$76,521 |
| 84 Berlin | 0 | GS/OF | | | | | | 71 | \$32,859 |
| 85 Berlin | 0 | OF/CB | | | | | | 625 | \$287,571 |
| 86 Berlin | 0 | OF | | | | | | 110 | \$50,414 |
| 87 Berlin | 0 | OF | | | | | | 86 | \$39,554 |
| 88 Berlin | 0 | GS/WP | | | | | | 319 | \$146,514 |
| 89 Berlin | 0 | GS/CB | | | | | | 66 | \$30,271 |
| 90 Berlin | 0 | CB/GS/OF | | | | | | 134 | \$61,554 |
| 91 Berlin | 0 | GS | | | | | | 26 | \$11,872 |
| 92 Berlin | 0 | GS | | | | | | 12 | \$5,683 |
| 93 Berlin | 0 | GS/CB | | | | | | 66 | \$30,552 |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | | | (pg3) | | | | | |
|--|---------------|---|--|---------------|------------------------|--------------------------------------|---|--|---|--|----------------------------------|--------------------------------|
| Watershed Number | Action List # | Proposed Action | Proposed or Existing Stormwater Treatment Practice | Permit Number | Watershed Area (Acres) | Percent Mapped Impervious Area (MIA) | Sediment Load with Current Reductions (lbs) | Sediment Load with Priority Action (lbs) | Phosphorus Load with Current Reductions (lbs) | Phosphorus Load with Priority Action (lbs) | Water Quality Volume (Acre-Feet) | Channel Protection (Acre-Feet) |
| 94 Berlin | | | CB/GS/SB | 5624-9010 | 5.3 | 23 | 703 | 703 | 2.0 | 2.0 | 0.04 | 0.14 |
| 95 Berlin | | | GS | | 14.9 | 10 | 1,519 | 1,519 | 4.2 | 4.2 | 0.09 | 0.16 |
| 96 Berlin | | | GS | | 1.6 | 26 | 371 | 371 | 1.0 | 1.0 | 0.02 | 0.05 |
| 97 Berlin | 2 | Extended Detention Pond below Green Mt Drive outfall | EDPMP/GS/OF | | 4.6 | 30 | 1,241 | 248 | 3.4 | 2.1 | 0.07 | 0.16 |
| 98 Berlin | | | GS/CB/OF | 5624-9010 | 7.5 | 22 | 1,184 | 1,184 | 3.3 | 3.3 | 0.07 | 0.18 |
| 99 Berlin | | | CB | 5624-9010 | 6.1 | 17 | 764 | 764 | 2.1 | 2.1 | 0.04 | FALSE |
| 100 Berlin | | | CB/GS | | 8.2 | 39 | 3,695 | 3,695 | 10.3 | 10.3 | 0.21 | FALSE |
| 101 Berlin | | | CB | | 5.5 | 62 | 4,113 | 4,113 | 11.4 | 11.4 | 0.23 | FALSE |
| 102 Berlin | 1 | Sand Filter or Extended Detention Basin in Vtrans district garage yard/Stormwater Pollution Prevention Plan | EDP/SF/SWPPP/C B | | 3.9 | 71 | 3,387 | 677 | 9.4 | 5.6 | 0.19 | FALSE |
| 103 Berlin | | | CB | | 0.8 | 86 | 806 | 806 | 2.2 | 2.2 | 0.05 | FALSE |
| 104 Berlin | | | GS/CB | | 22.1 | 21 | 4,003 | 4,003 | 11.1 | 11.1 | 0.23 | 0.51 |
| 105 Berlin | | | CB | | 1.5 | 74 | 1,392 | 1,392 | 3.9 | 3.9 | 0.08 | FALSE |
| 106 Berlin | | | CB | | 1.1 | 72 | 940 | 940 | 2.6 | 2.6 | 0.05 | FALSE |
| 107 Berlin | | | CB/GS | | 12.6 | 28 | 2,999 | 2,999 | 8.3 | 8.3 | 0.17 | FALSE |
| 108 Berlin | | | CB/GS | | 3.7 | 57 | 2,156 | 2,156 | 6.0 | 6.0 | 0.12 | FALSE |
| 109 Berlin | 3 | Sand Filter or Extended Detention Basin, combine with 110 | SF/EDP/CB/GS | | 7.1 | 53 | 4,478 | 896 | 12.4 | 7.5 | 0.25 | FALSE |
| 110 Berlin | 3 | Sand Filter or Extended Detention Basin, combine with 109 | SF/EDP/CB/GS | | 12.4 | 64 | 9,581 | 1,916 | 26.6 | 16.0 | 0.54 | FALSE |
| 111 Berlin | 1 | Bioretention on either side of entrance to shopping center | BRA/CB/GS | | 5.0 | 62 | 3,703 | 741 | 10.3 | 6.2 | 0.21 | FALSE |
| 112 Berlin | | | CB/GS | | 18.0 | 24 | 5,156 | 5,156 | 14.3 | 14.3 | 0.29 | 0.48 |
| 113 Berlin | | | CB/GS | | 22.1 | 17 | 3,277 | 3,277 | 9.1 | 9.1 | 0.19 | 0.41 |
| 114 Berlin | | | CB | | 13.2 | 30 | 3,428 | 3,428 | 9.5 | 9.5 | 0.19 | 0.43 |
| 115 Berlin | 1 | Sedimentation Basin and pipe conveyance needed. Water overflows area. | SB/SD/CB | | 18.5 | 14 | 2,319 | 1,159 | 6.4 | 5.2 | 0.13 | FALSE |
| 116 Berlin | | | CB/RS | | 5.9 | 10 | 612 | 612 | 1.7 | 1.7 | 0.03 | FALSE |
| 117 Berlin | | | CB/IG | | 4.5 | 38 | 1,539 | 1,539 | 4.3 | 4.3 | 0.09 | FALSE |
| 118 Berlin | | | CB/GS | | 12.9 | 16 | 1,803 | 1,803 | 5.0 | 5.0 | 0.10 | FALSE |
| 119 Berlin | | | CB/GS | 3717-9010 | 19.6 | 45 | 10,334 | 10,334 | 28.7 | 28.7 | 0.58 | FALSE |
| 120 Berlin | | | GS/CB | | 24.8 | 12 | 2,843 | 2,843 | 7.9 | 7.9 | 0.16 | FALSE |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | (pg3) | | | | |
|--|---------------|--|-----------------------------------|---------------------------------------|--|--|------------------------|---|-----------------|
| Watershed Number | Action List # | Proposed or Existing Stormwater Treatment Practice | Estimated Basin Construction Cost | Estimated Other BMP Construction Cost | Cost of Sediment Removal Per Pound (based on annual sediment load) | Cost of Phosphorus Removal Per Pound (based on annual phosphorus load) | Assistance Program | Number of LID - Roof Raingardens to treat CPv (Residential) | Raingarden Cost |
| 94 Berlin | 0 | CB/GS/SB | | | | | | 69 | \$31,621 |
| 95 Berlin | 0 | GS | | | | | | 79 | \$36,291 |
| 96 Berlin | 0 | GS | | | | | | 24 | \$10,859 |
| 97 Berlin | 2 | EDPMP/GS/OF | 21,413.45 | | \$22 | \$15,527 | ERP, Section 319, LCBP | 78 | \$35,841 |
| 98 Berlin | 0 | GS/CB/OF | | | | | | 91 | \$41,805 |
| 99 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 100 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 101 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 102 Berlin | 1 | EDP/SF/SWPPP/CB | 58,431.65 | | \$22 | \$15,527 | ERP, Section 319, LCBP | 0 | \$0 |
| 103 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 104 Berlin | 0 | GS/CB | | | | | | 255 | \$117,425 |
| 105 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 106 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 107 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 108 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 109 Berlin | 3 | SF/EDP/CB/GS | 242,549.62 | | \$22 | \$15,527 | ERP, Section 319, LCBP | 0 | \$0 |
| 110 Berlin | 3 | SF/EDP/CB/GS | Combine with 110 | | | | | 0 | \$0 |
| 111 Berlin | 1 | BRA/CB/GS | 48,192.29 | | \$16 | \$11,712 | ERP, Section 319, LCBP | 0 | \$0 |
| 112 Berlin | 0 | CB/GS | | | | | | 241 | \$110,955 |
| 113 Berlin | 0 | CB/GS | | | | | | 204 | \$93,794 |
| 114 Berlin | 1 | SB/SD/CB | | | | | | 216 | \$99,252 |
| 115 Berlin | 1 | SB/SD/CB | 40,001.31 | | \$35 | \$31,053 | ERP, Section 319, LCBP | 0 | \$0 |
| 116 Berlin | | CB/RS | | | | | | 0 | \$0 |
| 117 Berlin | | CB/IG | | | | | | 0 | \$0 |
| 118 Berlin | | CB/GS | | | | | | 0 | \$0 |
| 119 Berlin | | CB/GS | | | | | | 0 | \$0 |
| 120 Berlin | | GS/CB | | | | | | 0 | \$0 |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | | | (pg4) | | | | | |
|--|---------------|--|--|---------------|------------------------|--------------------------------------|---|--|---|--|----------------------------------|--------------------------------|
| Watershed Number | Action List # | Proposed Action | Proposed or Existing Stormwater Treatment Practice | Permit Number | Watershed Area (Acres) | Percent Mapped Impervious Area (MIA) | Sediment Load with Current Reductions (lbs) | Sediment Load with Priority Action (lbs) | Phosphorus Load with Current Reductions (lbs) | Phosphorus Load with Priority Action (lbs) | Water Quality Volume (Acre-Feet) | Channel Protection (Acre-Feet) |
| 121 Berlin | 1 | Bioretention area at 451 Partridge Farm Rd and near RR crossing at 149 Partridge Farm Rd | BRA/GS | 3147-9010 | 61.1 | 9 | 5,212 | 1,042 | 14.5 | 8.7 | 0.29 | FALSE |
| 122 Berlin | | | GS | 3147-9010 | 2.2 | 27 | 424 | 424 | 1.2 | 1.2 | 0.02 | FALSE |
| 123 Berlin | | | OF | 5160-9010 | 79.6 | 2 | 5,518 | 5,518 | 15.3 | 15.3 | 0.31 | 0.16 |
| 124 Berlin | | | OF/GS | 3170-9010 | 9.9 | 44 | 4,115 | 4,115 | 11.4 | 11.4 | 0.23 | FALSE |
| 125 Berlin | | | OF/GS | | 19.2 | 10 | 1,951 | 1,951 | 5.4 | 5.4 | 0.11 | FALSE |
| 126 Berlin | | | OF | | 4.4 | 44 | 2,225 | 2,225 | 6.2 | 6.2 | 0.13 | FALSE |
| 127 Berlin | | | CB/GS | 3717-9010 | 19.9 | 27 | 6,220 | 6,220 | 17.3 | 17.3 | 0.35 | FALSE |
| 128 Berlin | | | CB | | 1.3 | 87 | 1,364 | 1,364 | 3.8 | 3.8 | 0.08 | FALSE |
| 129 Berlin | | | CB/GS | | 2.5 | 74 | 2,243 | 2,243 | 6.2 | 6.2 | 0.13 | FALSE |
| 130 Berlin | | | CB/GS | | 12.0 | 11 | 1,306 | 1,306 | 3.6 | 3.6 | 0.07 | FALSE |
| 131 Berlin | | | CB | | 2.7 | 65 | 2,102 | 2,102 | 5.8 | 5.8 | 0.12 | FALSE |
| 132 Berlin | | | GS | | 2.5 | 37 | 1,059 | 1,059 | 2.9 | 2.9 | 0.06 | FALSE |
| 133 Berlin | | | CB/GS | | 8.0 | 30 | 2,126 | 2,126 | 5.9 | 5.9 | 0.12 | FALSE |
| 134 Berlin | | | OF | | 8.9 | 14 | 1,144 | 1,144 | 3.2 | 3.2 | 0.06 | FALSE |
| 136 Berlin | | | CB/GS | | 26.5 | 18 | 4,114 | 4,114 | 11.4 | 11.4 | 0.23 | FALSE |
| 137 Berlin | | | OF/GS | | 26.1 | 17 | 3,868 | 3,868 | 10.7 | 10.7 | 0.22 | FALSE |
| 138 Berlin | | | OF/GS | | 5.1 | 39 | 1,798 | 1,798 | 5.0 | 5.0 | 0.10 | FALSE |
| 139 Berlin | | | GS/CB | | 45.6 | 8 | 4,243 | 4,243 | 11.8 | 11.8 | 0.24 | FALSE |
| 140 Berlin | 1 | Stabilize erosion on both sides of Highland Ave and down to Rte 302 | RR/OF/GS/CB | | 59.6 | 6 | 5,068 | 3,547 | 14.1 | 12.7 | 0.29 | FALSE |
| 141 Berlin | | | GS | | 1.9 | 29 | 647 | 647 | 1.8 | 1.8 | 0.04 | FALSE |
| 142 Berlin | | | OF | | 1.6 | 36 | 516 | 516 | 1.4 | 1.4 | 0.03 | FALSE |
| 143 Berlin | | | OF | | 2.9 | 52 | 1,802 | 1,802 | 5.0 | 5.0 | 0.10 | FALSE |
| 144 Berlin | | | OF | | 7.3 | 11 | 804 | 804 | 2.2 | 2.2 | 0.05 | FALSE |
| 145 Berlin | | | OF/CB | | 6.4 | 32 | 1,813 | 1,813 | 5.0 | 5.0 | 0.10 | FALSE |
| 146 Berlin | 1 | Stabilize erosion below Rte 62, Extended Detention Basin for west drainage on west side of outfall | RR/EDP/OF/CB | | 1353.1 | 2 | 92,875 | 55,725 | 258.0 | 206.4 | 5.25 | 2.34 |
| 147 Berlin | | | CB/GS | 5160-9010 | 115.4 | 7 | 10,177 | 10,177 | 28.3 | 28.3 | 0.58 | 0.88 |
| 148 Berlin | | | CB/GS | | 49.1 | 2 | 3,475 | 3,475 | 9.7 | 9.7 | 0.20 | FALSE |
| 149 Berlin | | | CB/GS | | 92.6 | 7 | 8,172 | 8,172 | 22.7 | 22.7 | 0.46 | FALSE |
| 150 Berlin | | | CB | | 17.4 | 5 | 1,417 | 1,417 | 3.9 | 3.9 | 0.08 | FALSE |
| 151 Berlin | | | CB | | 14.6 | 4 | 1,088 | 1,088 | 3.0 | 3.0 | 0.06 | FALSE |
| 152 Berlin | | | CB | | 127.3 | 1 | 8,685 | 8,685 | 24.1 | 24.1 | 0.49 | 0.19 |
| 153 Berlin | 2 | Combine with 13.21 | EDPMP/WP/EDP/CB/GS | 6458-9015 | 12.5 | 36 | 1,918 | 959 | 6.5 | 4.5 | 0.16 | 0.49 |
| 154 Berlin | | | CB/GS | 4582-9010 | 10.6 | 37 | 2,989 | 2,989 | 8.3 | 8.3 | 0.17 | 0.42 |
| 175 Berlin | | | CB | 4820-9010 | 2.1 | 74 | 1,893 | 1,893 | 5.3 | 5.3 | 0.11 | 0.17 |

| Berlin - Subwatershed Prioritization and Recommendations | | | | | (pg4) | | | | |
|--|---------------|--|-----------------------------------|---------------------------------------|--|--|------------------------|---|-----------------|
| Watershed Number | Action List # | Proposed or Existing Stormwater Treatment Practice | Estimated Basin Construction Cost | Estimated Other BMP Construction Cost | Cost of Sediment Removal Per Pound (based on annual sediment load) | Cost of Phosphorus Removal Per Pound (based on annual phosphorus load) | Assistance Program | Number of LID - Roof Raingardens to treat CPv (Residential) | Raingarden Cost |
| 121 Berlin | 1 | BRA/GS | 67,822.10 | | \$16 | \$11,712 | ERP, Section 319, LCBP | 0 | \$0 |
| 122 Berlin | 0 | GS | | | | | | 0 | \$0 |
| 123 Berlin | 0 | OF | | | | | | 81 | \$37,416 |
| 124 Berlin | 0 | OF/GS | | | | | | 0 | \$0 |
| 125 Berlin | 0 | OF/GS | | | | | | 0 | \$0 |
| 126 Berlin | 0 | OF | | | | | | 0 | \$0 |
| 127 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 128 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 129 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 130 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 131 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 132 Berlin | 0 | GS | | | | | | 0 | \$0 |
| 133 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 134 Berlin | 0 | OF | | | | | | 0 | \$0 |
| 136 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 137 Berlin | 0 | OF/GS | | | | | | 0 | \$0 |
| 138 Berlin | 0 | OF/GS | | | | | | 0 | \$0 |
| 139 Berlin | 0 | GS/CB | | | | | | 0 | \$0 |
| 140 Berlin | 1 | RR/OF/GS/CB | | 5,000.00 | \$3 | \$3,552 | ERP, Section 319, LCBP | 0 | \$0 |
| 141 Berlin | 0 | GS | | | | | | 0 | \$0 |
| 142 Berlin | 0 | OF | | | | | | 0 | \$0 |
| 143 Berlin | 0 | OF | | | | | | 0 | \$0 |
| 144 Berlin | 0 | OF | | | | | | 0 | \$0 |
| 145 Berlin | 0 | OF/CB | | | | | | 0 | \$0 |
| 146 Berlin | 1 | RR/EDP/OF/CB | 140,000.00 | 15,000.00 | \$4 | \$3,004 | ERP, Section 319, LCBP | 1,172 | \$539,189 |
| 147 Berlin | 0 | CB/GS | | | | | | 442 | \$203,342 |
| 148 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 149 Berlin | 0 | CB/GS | | | | | | 0 | \$0 |
| 150 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 151 Berlin | 0 | CB | | | | | | 0 | \$0 |
| 152 Berlin | 0 | CB | | | | | | 96 | \$44,224 |
| 153 Berlin | 2 | EDPMP/WP/EDP/CB/C | Combine with 13, 21 | | | | | 246 | \$113,149 |
| 154 Berlin | 0 | CB/GS | | | | | | 212 | \$97,676 |
| 175 Berlin | 0 | CB | | | | | | 85 | \$39,316 |


Target Maps

*Showing Priority Action List
Drainage Areas*

And Potential Retrofit Locations

Subwatershed: 102
Action List: 1

Potential for a Sedimentation Basin or an Extended Detention Pond below at the VTrans district garage to treat the runoff from subwatershed #102.



Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Dry Well
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012




Subwatershed: 109 & 110
Action List: 3

Subwatershed: 111
Action List: 1

Potential for a Sand Filter or Extended Detention Basin to treat the runoff from subwatersheds #109 and #110.

Potential to for a Bioretention Area to treat the runoff from subwatershed #111 before it enters the receiving water.




Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.




- | | | |
|---|--|---|
| <p>Point Features</p> <ul style="list-style-type: none"> Catchbasin Dry Well Drop Inlet Stormwater Manhole Yard drain Outfall Culvert inlet Culvert outlet Retrofit <p>Area Features</p> <ul style="list-style-type: none"> Priority Subwatershed Stormwater Treatment Area Potential Stormwater Treatment Area | <p>Line Features</p> <ul style="list-style-type: none"> Storm line Swale Stream Footing drain Under drain Roof drain Trench drain Tunnel (storm) Emergency spillway | <p>NRCS - Soils</p> <ul style="list-style-type: none"> A B C D |
|---|--|---|

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012



Subwatershed: 115
Action List: 1

Potential for a Sedimentation Basin and Pipe Conveyance to treat the runoff from subwatershed #115.




Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway


NRCS - Soils

- A
- B
- C
- D


Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012



Subwatershed: 121
Action List: 1



Potential for a Bioretention Area at 451 Partridge Farm Road to treat the runoff from subwatershed #121.




Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Dry Well
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils


- A
- B
- C
- D

Area Subwatershed

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012





Potential for a Bioretention Area in the median of Route 62 to treat the runoff from subwatersheds #20.

Potential for a retrofit to the outlet of the Extended Detention Pond to treat the runoff from subwatersheds #13, #20, #21, and #153.

Subwatershed: 13, 20, 21, & 153
Action List: 2


Subwatershed: 20
Action List: 2

Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.





- | | | | | | |
|-----------------------|-------------------------------------|----------------------|--------------------|---------------------|---|
| Point Features | | Line Features | | NRCS - Soils | |
| | Catchbasin | | Storm line | | A |
| | Dry Well | | Swale | | B |
| | Drop Inlet | | Stream | | C |
| | Stormwater Manhole | | Footing drain | | D |
| | Yard drain | | Under drain | | |
| | Outfall | | Roof drain | | |
| | Culvert inlet | | Trench drain | | |
| | Culvert outlet | | Tunnel (storm) | | |
| | Retrofit | | Emergency spillway | | |
| Area Features | | | | | |
| | Priority Subwatershed | | | | |
| | Stormwater Treatment Area | | | | |
| | Potential Stormwater Treatment Area | | | | |

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012



Subwatershed: 140
Action List: 1




Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Dry Well
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features



- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012



Subwatershed: 146
Action List: 1

Potential for Slope Stabilization and an Extended Detention Pond to treat the runoff from subwatershed #146.



Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Dry Well
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
DEC - WSMD - Ecosystem Restoration Section

Plotted Date: 4/16/2013

Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database

Imagery Source: NAIP 2012



Agency of Natural Resources

Subwatershed: 60
Action List: 2

Potential for a Bioretention Area to treat the runoff from subwatershed #60.




Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- ▣ Catchbasin
- Drop Inlet
- Stormwater Manhole
- Yard drain
- ⊙ Outfall
- Culvert inlet
- Culvert outlet
- Ⓟ Retrofit

Line Features

- Storm line
- ↗ Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- ⊙ Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012



Subwatershed: 62
Action List: 2

Potential for a Bioretention Area below rear parking area to treat the runoff from subwatershed #62.



Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section


Plotted Date: 4/16/2013

Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database

Imagery Source: NAIP 2012



Subwatershed: 66
Action List: 1




Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D


Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
DEC - WSMD - Ecosystem Restoration Section
Plotted Date: 4/16/2013
Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
Imagery Source: NAIP 2012



Subwatershed: 73
Action List: 1




Potential for an Extended Detention Pond to treat the runoff from subwatershed #73.

Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section
 Plotted Date: 4/16/2013
 Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database
 Imagery Source: NAIP 2012



Subwatershed: 97
Action List: 2



Berlin, VT

DEC Stormwater Infrastructure Mapping Project

This map shows high priority subwatersheds which are ranked by connectedness, percent of impervious cover, field observations, and potential retrofit measures and locations.

The data shown on this map is only as accurate as the available sources and field observations allowed and should be used as a basic planning level tool only.



Point Features

- Catchbasin
- Dry Well
- Drop Inlet
- Stormwater Manhole
- Yard drain
- Outfall
- Culvert inlet
- Culvert outlet
- Retrofit

Line Features

- Storm line
- Swale
- Stream
- Footing drain
- Under drain
- Roof drain
- Trench drain
- Tunnel (storm)
- Emergency spillway

NRCS - Soils

- A
- B
- C
- D

Area Features

- Priority Subwatershed
- Stormwater Treatment Area
- Potential Stormwater Treatment Area

Creator: Jim Pease, David Ainley
 DEC - WSMD - Ecosystem Restoration Section

Plotted Date: 4/16/2013

Data Sources: VTRANS Roads data, VT Hydrography data set, DEC Stormwater database

Imagery Source: NAIP 2012



Spill Control

and

*Vermont Hazardous Waste Management
Regulations*

Have a spill control plan for accidental spills at municipal facilities and on municipal streets

These stormwater infrastructure maps show the connectivity of the stormwater system for the municipality as accurately as it could be determined with the collected and existing data. In the event of a spill this can be a valuable tool for controlling spills and in spill response.

Towns should be equipped with suitable equipment to contain and clean up spills of hazardous materials. Accidental spills of materials can be sources of runoff pollution if not addressed appropriately. If possible Towns should be prepared to address spills on municipal streets while at the same time contacting the state Waste Management Division. DPW managers should be aware of all applicable requirements and should contact regulatory authorities if requirements are not known.

All spills should be cleaned up immediately after they occur. For municipal facilities the creation of a site specific spill control and response plan in combination with spill response training for designated on-site personnel can be effective in dealing with accidental spills and preventing the contamination of soil, water, and runoff. Preparation of a spill containment, control, and countermeasures (SPCC) plan might be required to meet regulatory requirements (e.g., requirements regarding storage of specified chemicals above certain volume thresholds).

Even if a formal plan is not required, preparing one is a good idea. In general, an SPCC plan should include guidance to site personnel on the following:

- Proper notification when a spill occurs;
- Site responsibility with respect to addressing the cleanup of a spill;
- Stopping the source of a spill;
- Cleaning up a spill;
- Proper disposal of materials contaminated by the spill;
- Location of spill response equipment programs; and
- Training for designated on-site personnel.



A periodic spill “fire drill” should be conducted to help prepare Town personnel in the event of a spill.

Spill Prevention and Response Measures

Catch Basin Inserts

Catch Basin Inserts (Drain Guards / Sediment Traps) protect our rivers and streams by capturing sediment, debris, oil and grease at storm water catch basins. Catch Basin Inserts are an economical and effective method to protect you from costly clean-up work.

The standard filter material is a non-woven geotextile with built-in overflow ports for cases of abnormally high water flow or over-filled filter bags. Catch Basin Inserts are available with a replaceable 5” x 15” oil absorbent boom that floats to absorb any oil, gas or diesel entering a storm water catch basin.



Urethane Drain Protector

Urethane Drain Protectors are positive sealing drain covers that ensure spills do not enter drains. Drain Protectors are environmentally safe and resistant to chemicals, solvents and hydrocarbons. After use, the Drain Protector can be washed and stored in its tube storage container.



Absorbent Socks

Absorbent socks are flexible tubes used to contain and clean-up spilled fluids. Socks are widely used in industrial applications and are ideal for Spill Kits. Fast spreading spills are quickly stopped with a sock.



Drums & Intermediate Bulk Containers (IBC's)



New and reconditioned steel drums are ideal for storing solid and liquid waste. Poly drums available for durable outdoor storage or for building your own spill kits. Steel and poly drums are available in both tight-head (TH) and full open-head styles (FOH).



Pads & Rolls

Absorbent pads and rolls made from polypropylene fibers are the most popular form of absorbents on the market. Various types of absorbent pads and rolls can be used for different liquids and site applications.

The most widely used absorbent pads and rolls are oil-only (white) and universal (grey). Pads and rolls are great for spills on land, easily absorbing 20 to 25 times their own weight in recovered liquid. Rolls can easily be cut to the exact size required.



water or

Booms

Linkable Absorbent Booms

Absorbent booms are ideal for containing and cleaning up spills on water. Booms repel water and float even when completely saturated. Absorbent booms are constructed with a strong mesh outer skin encasing non-linting and highly absorbent polypropylene filler. Linkable booms come complete with end rings and clips attached to nylon rope running the length of the boom.



Collection basins

Collection basins are permanent structures in which large spills or contaminated storm water is contained and stored before cleanup or treatment. Collection basins are designed to receive spills, leaks, etc., and to prevent pollutants from being released into the environment. Unlike containment dikes, collection basins can receive and contain materials from many locations across a facility.

Containment diking

Containment dikes are temporary or permanent earth or concrete berms or retaining walls that are designed to hold spills. Diking can be used at any industrial facility, but is most common for controlling large spills or releases from liquid storage and transfer areas. Diking can provide one of the best protective measures against the contamination of storm water because it surrounds the area of concern and keeps spilled materials separated from the storm water outside of the diked area.

Curbing

Similar to containment diking, a curb is a barrier that surrounds an area of concern. Unlike diking, curbing is unable to contain large spills and is usually implemented on a small-scale basis. However, curbing is common at many facilities and in small areas where liquids are handled and transferred.

Granular Absorbents

A variety of granular and powdered absorbents are available for the effective clean-up of spills on streets, construction sites and in repair shops. These products absorb spilled liquids of various kinds to greatly lower the viscosity, aiding in the clean-up of the spill.

Sorbents, Gels, and Foams

Sorbents are compounds that immobilize materials by surface absorption or adsorption in the sorbent bulk. Gelling agents interact with the spilled chemical(s) by concentrating and congealing to form a rigid or viscous material more conducive to a mechanical cleanup. Foams are mixtures of air and aqueous solutions of proteins and surfactant-based foaming agents. The primary purpose of foams is to reduce the vapor concentration above the spill surface, thereby controlling the rate of evaporation.

§ 7-105 EMERGENCY AND CORRECTIVE ACTIONS

(a) Emergency actions

(1) In the event of a discharge of hazardous waste or a release of a hazardous material, the person in control of such waste or material shall:

(A) Take all appropriate immediate actions to protect human health and the environment including, but not limited to, emergency containment measures and notification as described below; and

(B) Take any further clean up actions as may be required and approved by federal, state, or local officials, or corrective actions as specified under **subsection (b)** of this section so that the discharged waste or released material and related contaminated materials no longer present a hazard to human health or the environment.

(2) Reporting

(A) All discharges and/or releases that meet any of the following criteria shall be immediately reported to the Secretary by the person or persons exercising control over such waste by calling the Waste Management Division at **(802) 241-3888**, Monday

through Friday, 7:45 a.m. to 4:30 p.m. or the Department of Public Safety, Emergency Management Division at **(800) 641-5005**, 24 hours/day:

(i) A discharge of hazardous waste, or release of hazardous material that exceeds 2 gallons;

(ii) A discharge of hazardous waste, or release of hazardous material that is less than or equal to 2 gallons and poses a potential or actual threat to human health or the environment; or

(iii) A discharge of hazardous waste, or release of hazardous material that equals or exceeds its corresponding reportable quantity under CERCLA as specified under **40 CFR § 302.4**.

Note: Under the Federal Water Pollution Control Act, certain spills of “oil” and/or “hazardous substances” are prohibited and must be reported pursuant to the requirements of **40 CFR Part 110** / Discharge of Oil. Certain spills of hazardous substances must also be reported pursuant to CERCLA. In both cases, the National Response Center must be notified at **(800) 424-8802**. Finally, in addition to federal and state spill reporting, EPCRA requires that spills are also reported to local authorities.

(B) A written report shall be submitted to the Secretary within ten (10) days following any discharge or release subject to **subsection (a)(1)** of this section. The report should be sent to: The Vermont Department of Environmental Conservation, Waste Management Division, 103 South Main Street, Waterbury, VT 05671-0404. The person responsible for submitting the written report may request that it not be submitted for small discharges and/or releases that were reported pursuant to subsection (a)(2)(A) of this section, and that have been entirely remediated within the ten (10) day period immediately following the discharge and/or release

(3) If the discharge or release occurred during transportation, the transporter shall, in addition to notifying the Secretary:

(A) Notify the National Response Center at (800) 424-8802 or (202) 426-2675, if required by **49 CFR § 171.15**; and

(B) Report in writing to the Director, Office of Hazardous Materials Regulations, Materials Transportation Bureau, Department of Transportation, Washington, D.C. 20590, if required by **49 CFR § 171.16**; and

(C) A water (bulk shipment) transporter who has discharged hazardous wastes must give the same notice as required by **33 CFR § 153.203** for oil and hazardous substances.

(4) If a discharge or release occurs and the Secretary determines that immediate removal of the waste is necessary to protect human health or the environment, the Secretary may authorize its removal by unpermitted transporters without the preparation of a manifest. Such hazardous waste may be transported to a site authorized by the Secretary under the provisions of **§ 7-503** to temporarily accept hazardous waste generated during an emergency cleanup of a discharge or release.

(5) In the case of an explosives or munitions emergency response, if a Federal, State, Tribal or local official acting within the scope of his or her official responsibilities, or an explosives or munitions emergency response specialist, determines that immediate removal of the material or waste is necessary to protect human health or the environment, that official or specialist may authorize the removal of the material or waste by transporters who do not have EPA identification numbers or hold Vermont hazardous waste transportation permits and without the preparation of a manifest. In the case of emergencies involving military munitions, the responding military emergency response specialist's organizational unit must retain records for three years identifying the dates of the response,

the responsible persons responding, the type and description of material addressed, and its disposition.

(6) All clean up debris and residues that are hazardous waste must be transported ultimately to either:

(A) A designated facility;

(B) A person authorized by the Secretary to use such waste if the waste has been delisted pursuant to § 7-218;

(C) Some other location specified and authorized by the Secretary to receive clean up debris and residues if the waste has been delisted pursuant to § 7-218; or

(D) For hazardous waste not defined as hazardous in 40 CFR Part 261 (i.e., waste regulated as hazardous by Vermont), to a facility, that is not a designated facility, located in a state other than Vermont provided the facility can receive such waste under applicable state and local laws, regulations and ordinances.

(b) Corrective actions

(1) If a discharge of hazardous waste, or a release of hazardous material has not been adequately addressed under **subsection (a)(1)(A)** of this section the Secretary may require that the person or persons responsible pursuant to **10 V.S.A. § 6615** complete the following:

(A) Engage the services of an environmental consultant experienced in the investigation and remediation of hazardous waste-contaminated sites; and

(B) Within thirty (30) days from either the date of the discharge/release or the date that the release was discovered if the date of discharge/release is not known, or within a period of time established by an alternative schedule approved by the Secretary, submit for approval by the Secretary a work plan for an investigation of the contaminated site (i.e., site investigation) prepared by the environmental consultant. The site investigation shall define the nature, degree and extent of the contamination; and shall assess potential impacts to human health and the environment (refer to the document titled: “Site Investigation Procedure” which is available from the Secretary upon request); and

(C) Perform the site investigation within either ninety (90) days of receiving written approval of the work plan by the Secretary, or a period of time established by an alternative schedule approved by the Secretary. A report detailing the findings of the site investigation shall be sent to the Secretary for review; and

(D) Within either thirty (30) days from the date of final acceptance of the site investigation report by the Secretary, or a period of time established by an alternative schedule approved by the Secretary, submit a corrective action plan prepared by the environmental consultant (refer to the document titled:

“Corrective Action Guidance” which is available from the Secretary upon request); and

(E) Implement the corrective action plan within either ninety (90) days of receiving written approval of the plan by the Secretary, or a period of time established by an alternative schedule approved by the Secretary. The corrective action activity shall continue until the contamination is remediated to levels approved by the Secretary; and

(F) Submit to the Secretary all investigative, corrective action and monitoring reports, and all analytical results related to subsections (b)(1)(C) through (E) of this section, as they become available.

(2) A used or fired military munition is a waste and is potentially subject to corrective action authorities pursuant to 10 V.S.A. § 6615, and the process described by subsection (b)(1) of this section if the munition lands off-range and is not promptly rendered safe or retrieved. Any imminent and substantial threats associated with any remaining material must be addressed. If remedial action is infeasible, the operator of the range must maintain a record of the event for as long as any threat remains. The record must include the type of munition and its location (to the extent the location is known).

§ 7-106 LAND DISPOSAL RESTRICTIONS

(a) Certain hazardous wastes shall not be disposed of in or on the land. **40 CFR Part 268**, which is hereby incorporated by reference, except for 40 CFR §§ 268.5, 268.6, and 268.42(b), identifies those wastes which shall not be land disposed and describes the limited circumstances under which an otherwise prohibited waste may continue to be land disposed. The authority for implementing the CFR sections not incorporated by reference remains with the EPA.

Note: A copy of 40 CFR Part 268 (the Land Disposal Restrictions rule), as incorporated by these regulations, is available from the Secretary upon request.

(b) In addition to the prohibitions of **40 CFR Part 268**, the Secretary may restrict the land disposal of any hazardous waste in the State of Vermont:

(1) Which may present an undue risk to human health or the environment, immediately or over a period of time; or

(2) Which would be incompatible with the **groundwater protection rule and strategy** of chapter 12 of the environmental protection rules.

(c) Dilution of hazardous waste subject to the land disposal restrictions of **40 CFR Part 268** is prohibited pursuant to **40 CFR § 268.3**.

§ 7-107 ENFORCEMENT

(a) Information that the generation, transportation, treatment, storage or disposal of hazardous waste may present an actual or potential threat to human health or the environment, or is a violation of the 10 V.S.A. chapter 159, or these regulations, or any term or condition of certification, order, or assurance, may serve as grounds for an enforcement action by the Secretary, including, but not limited to:

(1) After notice and opportunity for hearing, issuing an order directing any person to take such steps as are necessary to:

(A) Immediately cease and desist any operation or practice;

(B) Correct or prevent environmental damage likely to result from any deficiency in operation or practice;

(C) Suspend or revoke any certification and require temporary or permanent cessation of the operation of such facility;

(2) A request that the Attorney General or appropriate State's Attorney commence an action for injunctive relief, the imposition of penalties and fines provided in **10 V.S.A. § 6612** and other relief as may be appropriate.

(3) An order for reimbursement to any agency of federal, state, or local government from any person whose act caused governmental expenditures under **10 V.S.A § 1283**.

(4) All other powers of enforcement available to the Secretary through **10 V.S.A., chapter 201**.

(b) The hearing by the Secretary identified under **subsection (a)(1)** of this section shall be conducted as a contested case. Pursuant to **10 V.S.A. § 6610(b)**, the Secretary may issue an emergency order without a prior hearing when an ongoing violation presents an immediate threat of substantial harm to the environment or an immediate threat to public health. An emergency order shall be effective upon actual notice to the person against whom the order is issued. Any person to whom an emergency order is issued shall be given the opportunity for a hearing within five (5) business days of the date the order is issued.

(c) Inspections, investigations, and property access (**10 V.S.A. § 8005**)

(1) Inspections and investigations

(A) An investigator may perform routine inspections to determine compliance.

(B) An investigator may investigate upon receipt or discovery of information that an activity is being or has been conducted that may constitute or cause a violation.

(C) An investigator, upon presentation of credentials, may seek permission to inspect or investigate any portion of the property, fixtures, or other appurtenances belonging to or used by a person whose activity is required to be in compliance. The investigator shall state the purpose of the inspection or investigation. An inspection or investigation may include monitoring, sampling, testing, and copying of any records, reports, or other documents relating to the purposes to be served by compliance.

(D) If permission for an inspection or investigation is refused, the investigator may seek an access order from the district or superior court in whose jurisdiction the property is located enabling the investigator to perform the inspection or investigation.

(2) Access orders

(A) If access has been refused, an access order may be sought pursuant to either **10 V.S.A. § 8005** or **10 V.S.A. § 6609**.

(B) Issuance of an access order shall not negate the Secretary's authority to initiate criminal proceedings in the same matter by referring the matter to the office of the attorney general or a state's attorney.

(d) In an action to enforce these regulations, anyone raising a claim that a certain material is not a hazardous waste, or is exempt from regulation as hazardous waste, must demonstrate that there is a known market or disposition for the material, and that they meet the terms of the exclusion or exemption. Appropriate documentation (such as contracts showing that a second person uses the material as an ingredient in a production process) to demonstrate that the material is not a waste, or is exempt from regulation, must be provided. Owners and operators of facilities claiming that they are actually recycling materials must show that they have the necessary equipment to do so.