POTASH BROOK STORMWATER MANAGEMENT EVALUATION

Prepared For:
Lake Champlain Basin Program
54 West Shore Rd
Grand Isle, Vermont 05458

December 1997

Prepared By:
James Pease
Vermont Department of Environmental Conservation
Water Quality Division
10 North Building
103 S. Main Street
Waterbury, VT 05676

PART 2: Individual Watershed Stormwater Management Evaluations

The findings of this project are presented in the following individual watershed evaluations. The intent of reporting results in watershed format is to facilitate the incorporation of these findings into comprehensive watershed management plans for each of the project watersheds. These evaluations are not comprehensive management plans and should not be viewed as such. The intent is for these evaluations to serve to focus planning efforts and to provide a basis for evaluating specific implementation activities that will most likely result in environmental benefits in the form of minimized pollutant loadings to the target watersheds and to Lake Champlain and restoration of impaired riparian and aquatic habitat and the biologic communities that those habitats support. Above all, it is the hope of this project that these findings will stimulate the development of comprehensive multi-jurisdictional watershed planning efforts within the project area, resulting in watershed management conducted across political boundaries with full investment by local and regional authorities.

This project has assembled and/or created a number of Geographical Information System (GIS) data layers relevant to watershed planning in the project area (see Part I). Information from these data layers is presented in a series of figures attached to each watershed evaluation. These data layers with their associated data tables, will be available to local and regional planners. It should be recognized that the pollutant projections presented here are planning estimates and caution should be exercised when interpreting these values.

This project recognizes that local governments in the project area have made tremendous commitments to protecting and preserving the natural resources associated with surface waters. Local and regional planning, zoning, and conservation commissions have established a strong record of environmental concern. In order to fully realize effective watershed management, it is critical that individual missions, goals, objectives, and policies be consolidated under the umbrella of comprehensive watershed planing and management. It is hoped that the findings of this project will assist those responsible for planning and environmental management in the project area in their efforts to restore, protect, and preserve the aquatic resources of these highly vulnerable developing watersheds.

Potash Brook Stormwater Management Evaluation

Watershed Description

Potash Brook was originally called Louis Creek. This name was intended to honor the King of England's youngest son who later became Louis XIII of France. It was presumably later renamed for potash kilns built on or near the brook. Two dams were constructed on it although their use is unclear. The remains of both exist today, one is in UVM East Woods and one is on City of S. Burlington conservation lands adjacent to I-189. A sawmill was also once active at the Queen City Park Road crossing. Evidence of Algonquin Indians has been found in the watershed. Much of the watershed was converted from forest to agriculture in the late 18th and early 19th centuries. The beauty of the stream and its delta in Lake Champlain has been preserved in a painting by the 19th century Vermont artist CL Heyde entitled "View of Potash Brook and Shelburne Bay."

Potash Brook watershed is located in the city of South Burlington and encompasses an area of approximately 5300 acres (21 km2) (Figure 7.1). The stream rises in the city's growing southeast quadrant between Dorset and Spear Streets. It flows north and west through a series of wetlands and natural areas to Lake Champlain near Red Rocks beach. A northern tributary drains UVM agricultural lands and the Williston Road area of South Burlington.

Land Use

Current land use in the watershed (1995) is approximately 25% commercial-industrial, 35% residential, 30% agricultural and, 10% protected open space. Projected future land use designates the watershed as 20% subregional growth center, 30% industrial and 50% mixed urban use. The watershed is approximately 18% impervious (Figure 7.2, Table 7-1).

Table 7-1. Potash Brook: Current and Projected Land Use as percent watershed area. Projected land use is indicated in terms of zoning or planning categories.

	Open Protected	Ag	Res/Dev	Com/Ind	Urban/ Mixed	Regional Growth Center	Impervious Surface Area
1995	10%	30%	35%	25%	, s. :		18%
Projected				30%	50%	20%	

Soils

Highly erodible clays (Vergennes and Covington) are ubiquitous in the southeast quadrant of the watershed. Emphasis on best management practices during construction and stormwater controls that adequately remove sediment (infiltration, porous pavement, wetponds) would help to protect wetlands and water quality in the stream. Erodible soils are also present in the northwest corner of the watershed. Soils suitable for offline stormwater treatment ponds and wetlands are abundant throughout the watershed. Adams soils suitable for infiltration BMP's are also abundant in the northern half of the watershed as well as the west central section paralleling Farrell Street (Figures 7.3-5).

Riparian Corridor and Biological Evaluation

The riparian corridor of Potash Brook is in relatively good condition (Figure 7.6). However over

100 permitted and unpermitted stormwater discharges have caused a significant deterioration of the biological community in the lower watershed. The northern tributary is particularly degraded. The main stem has a series of protected natural areas that provide treatment and a recovery zone for stormwater pollutants. The southern tributaries are currently experiencing the greatest amount of development pressure and may degrade in the near future.

Potash Brook has severe sedimentation in the lower watershed and the north tributary (Figure 7.7). Evidence of sediment "plugs" exist in these reaches. The presence of wetlands and ponds in the middle reach has significantly reduced sediment levels in pools. Severe sedimentation impacts from interstate highway construction in the lower reach occurred between the years 1987-1992 but some recovery has occurred. Evidence of enrichment exists in the lower reach below the Shelburne Road stormwater discharges and in tributary 7 which is currently experiencing rapid growth and development.

Good pool habitat and healthy riparian habitat is reflected in the relatively strong fish populations in the brook. A project by the VT Fish and Wildlife Department to enhance fish habitat adjacent to I-189 appears to be successful (Langdon, personal communication). Macroinvertebrate sampling at 6 sites in the watershed indicates moderate sediment impacts and poor aquatic health with the exception of the reach between milepost 1-3. This reach is the only part of the stream which meets the Class B water quality standard for biological integrity (Figure 7.8).

Watershed Management Goals

The following are watershed management goals suggested by the findings of this evaluation:

- 1. Have in place the appropriate watershed planning and management infrastructure for the Potash Brook watershed such that comprehensive watershed management issues become an integral part of local planning processes. Watershed management should emphasize stream buffer protection, land acquisition, and watershed restoration.
- 2. Ensure the maintenance and protection of any existing high quality biological communities and habitats, including all existing wetlands, natural areas, and natural heritage sites through appropriate planning.
- 3. Ensure the protection of public water supplies and recreational beaches by minimizing the discharge of bacterial pollutants throughout the watershed.
- 4. Restore impaired aquatic and riparian habitat such that biological integrity consistent with Class B water quality standards is attained.
- 5. Ensure that watershed residents are aware of watershed management issues and are well educated in the principles of stream and watershed protection.
- 6. Minimize the discharge of pollutants from stormwater discharges in the Potash Brook watershed.

Existing Zoning

Potash Brook is located in S.Burlington and therefore is protected by a 100' conservation buffer (100'/side) on its main reach and a 50' buffer (50'/side) on its tributaries. New development is prohibited within the zone. Agriculture is exempt from the zone. The only active farm in the watershed, the University of Vermont Dairy Farm, has voluntarily agreed to maintain a 25'(25'/side) wildlife conservation buffer on the stream where it traverses the farm. The UVM East Woods Natural Area consisting of about 50 acres straddles the central reach of the stream and along with the Interstate-189 right of way protects a significant amount of riparian habitat. The city of S.Burlington's Farrell Park also protects a significant amount of habitat on one tributary of the stream.

Additional watershed features, including wetlands, 100 yr floodplain, Natural Heritage sites, natural biological areas and public lands, are mapped on Figure 7.8. Figure 7.9 shows mapped impervious surface, Figure 7.10 shows sewershed outlines, and Figure 7.11 shows nonpoint sources such as eroding banks, identified during watershed surveys.

Education Strategy

An education strategy for urban nonpoint source pollution should include the following actions: 1) informational mailings and public service announcements to watershed residents on clean stream habits, 2) public involvement in cleanup, erosion and habitat restoration projects, 3) storm drain stenciling, 4) school natural history programs and, 5) citizen monitoring (Drinkwin, 1995; Lake Champlain Committee, 1992).

Implementation Strategy

There are 11 targeted storm sewers and 7 targeted discharge permits in this watershed (Table 7-2, Figures 7.12-7.15). Seven of the sewers and 5 of the permits are located on sites highly suited for infiltration BMP's (map 3; Part 1). The remaining 4 sewers are located at the I-189-Shelburne Rd. cloverleaf. Wetpond BMP's are more suitable at this location due to soils and proximity to municipal swimming beaches (map 16; Part 1).

Implementation at all 11 storm sewers would result in a sediment reduction of 62,217 kg/yr and a phosphorus reduction of 82 kg/yr. Modification of the 7 discharge permits to include 5 infiltration systems and 2 wetponds would result in a TSS reduction of 40,285 kg/yr and a TP reduction of 47 kg/yr. The University Mall storm water permits are currently being modified for additional expansion and provide an optimal time for incorporating water quality goals.

Overall TSS and TP reduction from this strategy would be 66% and 54% respectively of existing load from the targeted sewersheds. Estimated capital cost for full implementation of this strategy ranges from \$87,657-\$687,098. A regional facility at the Shelburne Rd.-I-189 site would be the most economical strategy.

Implementation recommendations, estimated treatment efficiencies and loading reductions, and estimated capital and annualized capital costs are summarized in **Table 7-3.** Estimated annualized capital costs for phosphorus and suspended solids loading reductions at individual sites range from \$12 - \$1,705 per kg/yr for phosphorus and \$0.01 - \$1.50 per kg/yr for suspended solids.

Recommendations: The following recommendations, deriving from the findings of this evaluation, are made as technical suggestions that, if implemented, have a high likelihood of positively influencing water quality goals for the watershed. They are not intended to replace the development of a fully comprehensive watershed management plan.

- 1. The most significant recommendation that can be made here is for the establishment of a watershed planning process that will be able to incorporate the findings of this evaluation into a comprehensive watershed management plan. Such a plan would institutionalize stormwater and watershed management policies. Such a plan would also necessarily address the implementations issues such as prioritization and financing (Schueler, 1996).
- 2. Restoration of Impaired Habitat The most highly impacted areas in the watershed occur in the lower reach below Shelburne Road and in the heavily developed northern tributary. Riparian and aquatic habitat in these areas are impaired. It is likely that measures to reduce the release of sediments and suspended solids to this portion of the watershed through riparian habitat restoration and BMP implementation at targeted sewersheds will result in improved habitat and biological integrity. Therefore:
 - Additional feasibility studies for BMP implementation recommendations for targeted sewersheds

(Table 7-3), prioritized by estimated Total Suspended Solids loading (Table 7-2), should be initiated (see implementation strategy).

- Efforts to reduce discharges from significant sources of nonpoint sediment, such as eroding or unstable banks identified by this (Figure 7.11) or other evaluations, should be pursued. Opportunities to implement stream and riparian habitat restoration and improvement activities should be fully explored. Programs such as the Youth Conservation Corps and the USFW Partnership program are likely resources for implementing watershed restoration activities. Cooperative efforts between landowners and various State, private, and Federal Agencies should be encouraged and coordinated.
- 3. Coordination Resources should be allocated to provide for coordination of activities, including the acquisition of implementation resources, related to urban watershed management. VTDEC and USEPA are currently funding a limited service position to provide this function. If multi-jurisdictional urban watershed management is to be effective in the future, this function must be maintained, ideally through institutionalized regional planning.
- 4. Watershed Monitoring Continued monitoring of watershed condition should be conducted. BMP implementation effectiveness should be monitored. While VTDEC plans to maintain a minimal level of biological monitoring at many of the sites previously monitored, its resources are limited. Monitoring issues should be developed through the watershed planning process that should evolve at the regional or local level (Brown, 1996).
- 5. Education A watershed management educational strategy should be developed and implemented for the Indian Brook watershed. Generalized materials related to watershed protection are available from various private and governmental organizations (Lake Champlain Committee, 1992; Drinkwin, 1995).

Potash Brook Resources

Nutrient Loading to Shelburne Bay and St. Albans Bay, 1975-1976. 1977. K.Little. Department of Water Resources, Agency of Natural Resources, State of Vermont.

The Relations of Road Salt to Conditions in Potash Brook, Winter 1977-1978. 1979. Jerry Fagliano and George Terwilliger, Department of Zoology, University of Vermont, Burlington, Vermont.

<u>Fish Community Sampling In District 4.1990</u>. Memorandum from Biomonitoring and Aquatic Studies Section to Department of Fish and Wildlife, Agency of Natural Resources, State of Vermont.

<u>Potash Brook Tributary, South Burlington, Vermont, Watershed Model Report</u>. 1992. Lamoureux and Stone Consulting Engineers, Inc., Essex Junction, VT.

<u>Champlain Water District Discharge-Potash Brook</u>. 1994. Memorandum from Biomonitoring and Aquatic Studies Section to Permits, Compliance and Protection Division, Agency of Natural Resources, State of Vermont.

Muddy Brook, Boyer Quarry and Potash Source: A Miniplan for the Southeast Quadrant of South Burlington. 1972. South Burlington Natural Resources Committee, City of South Burlington, South Burlington, VT.

Unpublished data. 1995. Ray Belair, South Burlington Natural Resources Committee, City of South Burlington, South Burlington, VT.

Table 7-2. Significant Stormwater Discharges in the Potash Brook Watershed: Discharges are targeted based on estimated exceedence of annual loading thresholds for: suspended solids (4,536 kg/year); total phosphorus (6.8 kg/year); total metals (5.4 kg/year); total PAHs (36 kg/year); fecal coliform (500,000 colonies/yr). Existing treatment structures are indicated. *Italics indicate stormwater discharges with VTDEC stormwater permits*. EIA% is the percent surface area as Effective Impervious Surface Area. Loadings are calculated from the means of ranges in export coefficients taken from the literature. See Part 1 of this report for loading calculation methods.

Recwater	Storm sewershed	Treatment (Appendix 4)	EIA%	Loading kg/yr
	High	est Total Suspended So	olids	s gala
Potash San		CB/PP/GT/RS	84.6	20353 15728
	liston RdPinetree lington Interntl. Airport 4 liston Rd. 2	CB <i>CB/LU</i> CB	15.6 28.6 67.5	11584 10374 10312
Potash Km Potash Oak	art k Ridge-Butler Farm 2	CB GS	80.7 6.4	8875 8384
Potash She	ne Press-New England Telep. Iburne Road 7 ital Equipment Building 1	DP/CB CB DP/CB	34.6 80.6 57.5	7609 7283 7212
Potash Uni Potash Tim	iversity Mall 2 nber Lane	<i>CB/PP/GT/RS</i> CB	61.4 26.8	7162 7112
Potash She Potash Mil Potash Wil		CB CB CB	69.8 12.3 61.7	6896 6815 6396
Potash Lau Potash Cor	rel Hill Dr. porate Way 1	CB CB	12.5 57.6	6050 5988
Potash Gra	nth Burlington High School Indview Road 2 nehenge Drive	CB CB CB	64.2 100 8.7	5417 5080 4827
	indview Road 1	CB	43.5	4675

Table 7-	2 (cont)
----------	----------

			·		
Table 7-2 (co	nt)				1
Recwater	Storm sewershed	Treatment (Appendix 4) E	EIA%	Loading kg/yr	
		Hickory Total Dhambara			1
Potash Unive	rsity Mall 1	Highest Total Phosphorus		32	
Potash San R	•			25	
	ton RdPinetree			18	
Potash Burlin	igton Interntl. Airport 4			16	
Potash Willis	ton Rd. 2			16	
Potash Kmari	t ·			14	
	Ridge-Butler Farm 2			13	
	Press-New England Telep.			12	
Potash Shelbi				11	
	l Equipment Building 1			11	
Potash Unive				11	
Potash Shelbi			e to	11 11	
Potash Mills				11	
Potash Willis				10	
Potash Laure	l Hill Dr.			10	
Potash Corpo	orate Way 1		-	9	
	Burlington High School			9	
Potash Grand				8	
Potash Stonel				8	
Potash Grand	lview Road 1			7	•
	,	Highest Total PAH (Commercial Landuses Only	·)		
		Commercial Landases Omy	,		
Potash Unive	•			218	
Potash San R				168	
	gton Interntl. Airport 4			111	
Potash Willis				110	
Potash Kmari				94 82	
Potash Shelbi	Press-New England Telep.			82 78	
	l Equipment Building 1			78 77	
Potash Unive				77	
Potash Timbe	-			76	
Potash Shelbi	urne Road 8			74	
Potash Willis				68	
Potash Corpo				64	
	Burlington High School		•	58	
	gton Interntl. Airport 1		3.6	41	
Potash Burlin	igton Interntl. Airport 2	CB 2	1.0	40	

Table 7-2 (cont)

Recwat	er Storm sewershed	Treatment (Appendix 4) EIA%	Loading kg/yr
		Highest Total Metals	*********
Potash 1	University Mall 1	-	25
	San Remo Dr.		19
Potash `	Williston Rd-Pinetree		14
Potash 1	Burlington Interntl. Airport 4		13
	Williston Rd 2		13
Potash 1			11
	Oak Ridge-Butler Farm 2		10
	Lane Press-New England Telep.		9
	Shelburne Road 7		9
			9
	University Mall 2		9
	Timber Lane		9
	Shelburne Road 8		8
	Mills Ave		8
	Williston Rd		8
	Laurel Hill Dr.		7
	Corporate Way 1		7 .
	South Burlington High School		7
	Grandview Road 2		6
	Stonehenge Drive		6
Potash (Grandview Road 1		6
		Highest Total Fecal Coliform	
		(Colonies/year)	
	University Mall 1		3.2×10^6
	San Remo Dr.		2.5×10^6
	Williston RdPinetree		1.8×10^6
	Burlington Interntl. Airport 4		1.6×10^6
	Williston Rd. 2		1.6×10^6
Potash			1.4×10^6
	Oak Ridge-Butler Farm 2		1.3×10^6
	Lane Press-New England Telep.		1.2×10^6
	Shelburne Road 7		1.2×10^6
	Digital Equipment Building 1		1.1×10^6
	University Mall 2		1.1×10^6
	Timber Lane		1.1×10^6
	Shelburne Road 8		1.1×10^6
	Mills Ave		1.1×10^6
	Williston Rd. Laurel Hill Dr.		1.0×10^6 9.6×10^5
			9.6×10^{5}
	Corporate Way 1 South Burlington High School		8.7×10^{5}
	Grandview Road 2		8.1×10^{5}
	Stonehenge Drive		7.7×10^{5}
	Grandview Road 1		7.7×10^{5} 7.5×10^{5}
	Burlington Interntl. Airport 1	NAME OF BUILDING	6.2×10^{5}
	Burlington Interntl. Airport 2		6.0×10^{5}
	Sears 2	CB - 1.154 - 1.49.3	5.2×10^{5}
	Outlet Mall	CB 47.3	5.0×10^{5}

Table 7-3. Potash Brook Watershed: Stormwater BMP implementation treatment and capital costs estimates for targeted sewersheds.

All estimates are based on a mean of a range of export coefficients for TP and TSS.

		Polash	Polash	Potash	Potash	Potash	Potash	Potash (Potash	Potash	Potash	Potash	Potash	Potash	Potash	Potash	Potash	Potash	Polash		Rec. Wat.	
	-	Bl Airport 4	BI Airport 2	Bl Airport 1	Lane Press-NET	Univ. Mall 2	Univ. Mall 1	Oak RButler Fm2	San Remo Dr.	Williston Rd. Pine	Williston Rd.2	K-Mart	Shelburne Rd.7	Timber Lane	Shelburne Rd.8	Mills Ave.	Williston Rd.	Laurel Hill Dr.	Corporate Way		Sewershed	
TOTALS		Infiltration	Infiltration	Infiltration	Infiltration	Wetpond	Wetpond	Infiltration	Infiltration	Infiltration	Infiltration	Wetpond	Wetpond	Infiltration	Wetpond	Infiltration	Infiltration	Welpond	Infiltration		вмР	
238		16	6	6	12	11	32	9	25	18	16	14	1	1		11	10	10	9	Kgs/year	Pre BMP	ďΤ
109		7	2	2	5	6	18	5	10	7	6	8	6	4	6	4	4	5	4	Kgs/year	Post BMP	dТ
129		9	4	4	7	G	14	4	15		10	6	5	7	5	7	6	5	5	Kgs/year	Reduction	TD
154520		10374	3747	3852	7609	7162	20353	8384	15728	11584	10312	8875	7283	7112	6896	6815	6396	6050	5988	Kgs/year	Pre-BMP	Tee
52018		3112	1124	1156	2283	2865	8141	2515	4718	3475	3094	3550	2913	2134	2758	2044	1919	2420	1797	Kgs/year	Post-BMP	Tee
102502		7262	2623	2696	5326	4297	12212	5869	11010	8109	7218	5325	4370	4978	4138	4771	4477	3630	4191	Kgs/year	Reduction	Tee
\$87,657		\$7,562	\$3,519	\$1,624	\$4,729	\$1,334	\$2,516	\$17,472	\$4,351	\$13,659	\$3,517	\$1,282	\$1,054	\$5,478	\$1,141	\$9,504	\$2,370	\$4,183	\$2,362	dollars	Cost-Low)
\$687,098		\$45,374	\$21,112	\$9,742	\$28,373	\$26,687	\$50,327	\$104,829	\$26,107	\$81,956	\$21,102	\$25,643	\$21,074	\$32,868	\$22,827	\$57,027	\$14,218	\$83,659	\$14,173	dollars	Cost-High	7


Table 7-3. Potash Brook Watershed: Stormwater BMP implementation treatment and capital costs estimates for targeted sewersheds (cont).


\$44,697	\$5,702	\$0.44	\$0.06	\$346	\$44	\$7	\$0.86	\$5,326	\$680	AVERAGE
\$2,35Z	764¢	ФО.41	\$0.07	0700	ψÜÜ	é	÷	⊕ 0,042	0	7
))))))))		20.04	3 .	n n	9	A 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	67. 043	0783	RI Airport A
\$ 1 373	\$229	\$0.52	\$0.09	\$343	\$57	\$8	\$1.34	\$5,278	\$880	BI Airport 2
\$634	· \$106	\$0.24	\$0.04	\$158	\$26	\$4	\$0.60	\$2,436	\$406	BI Airport 1
\$1,846	\$308	\$0.35	\$0.06	\$264	\$44	\$5	\$0.89	\$4,053	\$676	Lane Press-NET
\$1,736	\$87	\$0.40	\$0.02	\$347	\$17	\$6	\$0.31	\$5,337	\$267	Univ. Mall 2
\$3,274	\$164	\$0.27	\$0.01	\$234	\$12	\$4	\$0.21	\$3,595	\$180	Univ. Mall 1
\$6,819	\$1,137	\$1.16	\$0.19	\$1,705	\$284	\$18	\$2.98	\$26,207	\$4,368	Oak RButler Fm2
\$1,698	\$283	\$0.15	\$0.03	\$113	\$19	\$2	\$0.40	\$1,740	\$290	San Remo Dr.
\$5,331	\$889	\$0.66	\$0.11	\$485	\$81	\$10	\$1.68	\$7,451	\$1,242	Williston Rd. Pine
\$1,373	\$229	\$0.19	\$0.03	\$137	\$23	\$ 3	\$0.49	\$2,110	\$352	Williston Rd.2
\$1,668	\$83	\$0.31	\$0.02	\$278	\$14	\$5	\$0.24	\$4,274	\$214	K-Mart
\$1,371	\$69	\$0.31	\$0.02	\$274	\$14	\$5	\$0.24	\$4,215	\$211	Shelburne Rd.7
\$2,138	\$356	\$0.43	\$0.07	\$305	\$ 51	\$7	\$1.10	\$4,695	\$783	Timber Lane
\$1,485	\$74	\$0.36	\$0.02	\$297	\$15	\$6	\$0.28	\$4,565	\$228	Shelburne Rd.8
\$3,710	\$618	\$0.78	\$0.13	\$530	\$88	\$12	\$1.99	\$8,147	\$1,358	Mills Ave.
\$925	\$154	\$0.21	\$0.03	\$154	\$26	\$3	\$0.53	\$2,370	\$395	Williston Rd.
\$5,442	\$272	\$1.50	\$0.07	\$1,088	\$54	\$23	\$1.15	\$16,732	\$837	Laurel Hill Dr.
\$922	\$154	\$0.22	\$0.04	\$184	\$31	\$3	\$0.56	\$2,835	\$472	Corporate Way
				٠						
High	Low	High	Low	High	Low	Dollars/kg	Dollars/kg	Dollars/kg	Dollars/kg	
30 Years @ 5%	30	30 yrs @ 5%	30	30 yrs @ 5%		High	Low	High	Low	Sewershed
Ted Coete	al Costs Total Annualized Costs	ק ה	Annual TSS c	Costs \$/ka	Annual TP Costs	TSS Cost	<i>Capital Costs/kg</i> TP Cost TSS Cost	TP Cost	TP Cost	
	•	:	•					0 : : - 1		

Appendices

POTASH BROOK AT REDROCKS BEACH

1988-1995(June-September)





Potash Brook






Figure 7.1: Potash Brook watershed showing roads and biological monitoring sites.






Figure 7.2: Potash Brook watershed 1995 actual land use; and future land use as defined by zoning designation.

Figure 7.3: Potash Brook generalized soils map.





Potash Brook - Highly Erodible Soils

Figure 7.4: Potash Brook watershed - areas of highly erodible soils. These soils are easily displaced.



Potash Brook - Wetpond/Wetland Soils

Figure 7.5: Potash Brook watershed - wetpond/wetland soils.



Riparian Corridor Evaluation (RCE)
Red=Poor, habitat structure gone
Brown=Fair, major habitat
alteration
Yellow=Good, minor habitat
alteration
Green=Very Good, monitor for
changes
Blue=Excellent, protect existing
status

Figure 7.6: Potash Brook Riparian Corridor Evaluation. Evaluation was conducted using the Riparian Corridor Evaluation methodology (Petersen, 1992). A series of measurements and observations are recording while walking the stream channel.





Figure 7.7: Potash Brook watershed - mapped wetlands, 100 yr. floodplain, biological natural areas, parks, and Natural Heritage sites.

Figure 7.8: Potash Brook watershed - biological condition. Fish and macroinvertebrate community measures of integrity. A macroinvertebrate biotic index (BI) rating of less than good is indicative of sub-Class B condition. A fish Index of Biotic Integrity (IBI) rating of less than 31 is indicative of sub-Class B condition.



Watershed measure of pool and riffle sedimentation. A high degree of sand embeddedness indicates excessive erosion and impairs aquatic habitat and the biological communities that are supported by that habitat.




Figure 7.9: Potash Brook watershed mapped impervious surface - 1996.




Figure 7.10: Potash Brook watershed mapped sewersheds - 1996.




Figure 7.11: Potash Brook watershed mapped nonpoint sources. Mapped sources include: nonpoint sources such as eroding banks identified during RCE; stormwater permitted discharges; EPA hot landuses (quik-stops with gas pumps, gas stations).

Targeted Stormwater Sewersheds Potash Brook Watershed




Figure 7.12: Targeted Stormwater Sewersheds in Potash Brook Watershed - Sewersheds were targeted based on exceedences of loading thresholds as described in Table 2.2. BMP recommendations are made for each targeted sewershed. Eighteen sewersheds in the Potash Brook watershed have been targeted.

Figure 7.13: Estimated total suspended solids loading from sewersheds in the Potash Brook watershed.







Figure 7.14: Estimated total phosphorus loading from sewersheds in the Potash Brook watershed.








Figure 7.15: Estimated total metals loading from sewersheds in the Potash Brook watershed. Graph at bottom shows concentrations of metals in whole (2mm) and fine fraction (63u) sediments at the mouth of the Potash watershed. Samples collected in 1995.





Soils AdA AdA AdA - AdB AdB - AdD AdD - AdE AdE - Au Au - BIA BIA - Br Br - Cv Cv - DdA DdA - EwA EwA - FaC FaC - FaE FaE - FsB FsB - Fu Fu - HIB HIB - HIE HIE - HnB HnB - Le Le - Lf Lf - MuD MuD - MyB MyB - MyC MyC - Rk Rk - ScB

> ScB - TeE TeE - W W - Wo



Land Use 1995
0
1100-Residential
1130-Residential-Single Famil
1190-Residential-Other
1200-Commercial
1230-Commercial Services
1250-Government
1252-Military
1260-Institutional
1270-Educational
The second control of
1281-Museum
1300-Industrial
1330-Industrial-Stone
1370-Industrial-Mining
1373-Sand/Gravel
1400-Transportation
1410-Transportation-Air
1412-Transportation-Air
1440-Transportaiton-Road
1460-Utilities
1470-Utilities
1480-Utilities
1481-Utilities
1482-Utilities
1500-Industrial
1510-Industrial Park
1600-Mixed Use
1700-Outdoor Built
1720-Outdoor Built
1730-Outdoor Recreation
1734-Ski Area
1735-Golf Course
1736-Campground
1737-Parks
1740-Cemetaries
1790-Other outdoor built
2100-Cropland
2200-Orchards
2430-Other Agriculture
3000-Brush
3300-Mixed Brush-grass
4100-Broadleaf Forest
4200-Coniferous Forest
4300-Mixed Forest
5100-Rivers
5200-Lakes/Ponds
5210-Lakes/Ponds
6000-Wetlands
6100-Forested Wetland
7200-Beaches/River banks
7400-Exposed Rock

•
Future Landuse
1200-Commercial
1500-Industrial
1600-Mixed Use
1700-Outdoor Built
1730-Outdoor Recreation
2100-Cropland
3000-Brush
4000-Forest
7000-Growth Center
7500-Subregional Growth Center